

Tremflex 25 LS

One part medium modulus polyurethane elastomeric sealant

Key Benefits Summary

- Wide movement accommodation $\pm 25\%$.
- Very flexible
- Rapid cure.
- Over paintable.
- Excellent adhesion to most common building substrates.
- Hard wearing.

Standards:

- ASTM C-920
- SNJF Class 1 Elastomeric

Product Information:

Description:

Tremflex 25 LS is a one part medium modulus polyurethane based elastomeric sealant.

Usage/Purpose:

- Perimeter sealing of windows.
- Curtain wall sealing.
- Masonry joints.
- Precast and tilt panel expansion/construction joints.
- Sealing of sheet metal and building claddings.
- General sealing of construction joints.

Limitations:

- Not suitable for prolonged immersion in water.
- Not suitable for wide joints subject to traffic.

Colour:

Grey, Black, White, Sand

Packaging:

Tremflex 25 LS is packaged in 600ml sausages (20 per carton).

Technical Information:

Composition:

Tremflex 25 SL is a one part moisture curing polyurethane sealant.

Characteristics:

Specific Gravity (at 25°C): Approx. 1.20
Hardness (ISO868/3sec): 25 Shore A

Performance (Typical Properties):

Service temperature range: -30°C to +90°C (cyclic)
Shrinkage: Negligible
Modulus: 0.30 MPa
Elongation @ break (ISO 8339):>250%
Slump Resistance (ISO 7390): Good
Skinning Time: > 6 hours
Movement (ISO 11600): $\pm 25\%$

Note: Typical properties should not be used as Specifications.

Usage Guidelines:

Joint Design Considerations:

Joint size should be 4 times the anticipated movement. For optimum performance, the width to depth ratio of Tremflex 25 LS should be 2:1 subject to a minimum depth of 10mm on porous substrates and 6mm on non-porous substrates. Sealant width should never be less than sealant depth. For fillet joints the minimum bite onto each surface should be 10mm for porous substrates and 6mm for non-porous substrates.

Substrate Preparation:

Joint faces should be clean, dry, sound and free from any contaminants likely to impair adhesion. Remove any loose or friable surfaces such as cement laitence etc. If necessary clean substrate with Xylol or Methyl Ethyl Ketone (MEK), do not use soap and water. If required, apply the recommended Tremco Primer and allow to dry.

Application:

Recommended application temperature range +5°C to +40°C. For cold weather application store the sausages at 20°C before using. Install an approved closed or open cell round polyethylene joint backing to control the depth of sealant. Use correct size backing rod to achieve recommended compression (20-30%). A self adhesive bond breaker tape can be used when the joint shape does not allow the use of joint backing. Dry tooling is recommended, immediately after application of sealant.

Priming:

Tremflex 25 LS does not need a primer for most building substrates. However, for new applications, field adhesion testing is recommended before commencement of the main installation. Tremco can also provide laboratory substrate adhesion tests at customer request.

Application:

Tremflex 25 LS is supplied in a non-sag consistency which guns easily using conventional skeleton guns for cartridge and full barrel bulk guns for sausages.

Coverage Rate:

Width	6mm	10mm	15mm	20mm	25mm
Depth					
6mm (min)	16	10	-	-	-
10mm	-	-	4	3	2.4
12mm (max)	-	-	-	-	2

Cleaning:

Remove excess sealant and smears adjacent to the joint (use masking tape where appropriate). Equipment may be cleaned with MEK, Xylol or Toluol, cured sealant can only be removed mechanically.

Health & Safety Precautions:

Avoid contact with skin and eyes. May cause irritation and skin sensitisation. Product contains flammable solvent. Always ensure adequate ventilation and keep away from flames and ignition sources. Material Safety Data Sheet must be read and understood before use.

Storage:

Store in shaded dry conditions between +5°C and +25°C.

Shelf Life:

9 months when stored as recommended in original unopened containers.

Guarantee/Warranty:

We warrant our products to be free of defects and manufactured to meet published physical properties when tested according to applicable specification and Tremco standards. Under this warranty we will provide at no charge, product to replace any product proven to be defective when applied in accordance with our written instructions and in applications recommended by Tremco as being suitable for this product. All claims concerning product defects must be made within 12 months of shipment. Absence of such claims in writing during this period will contribute a waiver of all claims with respect to such product. This warranty is in lieu of any and all other warranties expressed or compiled.

Equus Industries Ltd
PO Box 601
Blenheim
Phone: 03 578 0214 Fax 03 578 0919
Email: admin@equus.co.nz