



ARDEX TPO Universal and Large Pipe Flashing

Designed for flashing of round penetrations

ARDEX Australia Pty Ltd
20 Powers Road
Seven Hills NSW 2147
Tel: (02) 9851 9199
Fax: (02) 9674 5621
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX New Zealand Ltd
32 Lane St, Woolston
Christchurch, New Zealand
Tel: (03) 384 3029
Fax: (03) 384 9779
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX TPO Universal and Large Pipe Flashing

DESCRIPTION

ARDEX TPO Pipe Flashings are specifically designed to be used in roofing applications for flashing of round penetrations. Each pipe boot will fit various penetrations and shall be cut at the correct place to insure a tight fit before installation.

PREPARATION

Penetration shall be clean of prior flashings or foreign material.

APPLICATION

Select the pipe boot size that corresponds to the outside diameter of the penetration to be flashed. Cut out a circle on the outside of a level ring of the pipe boot that is smaller than the penetration.

Cut the extra material from the pipe boot base around the indented circle. Heat weld the boot into place and install the clamp and sealant per current ARDEX TPO specifications.

COVERAGE

1 piece per penetration.

CHARACTERISTICS

Physical

Material	Thermoplastic Polyolefin (TPO)
Colour	White or gray
Sizes	Universal (25.4 mm to 152.4 mm) Large (101.6 mm to 203.2 mm)

PACKAGING/STORAGE/SHELF LIFE

Pipe Boot Size	O/D of Penetration	Pieces per Carton
Universal	25.4 mm to 152.4 mm	10
Large	101.6 mm to 203.2 mm	10

NOTE: Clamps are included (All stainless steel – quick release – worm gear type).

Storage: Store material in its original unopened packaging away from sources of physical damage or chemical contamination.

Shelf life: Unlimited.

PRECAUTIONS

Exercise caution when lifting, moving, transporting, storing or handling ARDEX TPO Small and Large Pipe Flashing to avoid sources of punctures, physical damage or chemical contamination.

Refer to Material Safety Data Sheets for all applicable components of ARDEX TPO Systems.

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program.

Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations.

The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

ARDEX Australia Pty Ltd

New South Wales	Ph (02) 9851 9100	Fax (02) 9838 7970
Queensland	Ph (07) 3817 6000	Fax (07) 3881 3188
Victoria/Tasmania	Ph (03) 9308 9255	Fax (03) 9308 9332
South Australia	Ph (08) 8268 2511	Fax (08) 8345 3207
Western Australia	Ph (08) 9256 8600	Fax (08) 9455 1227

ARDEX New Zealand Ltd

Auckland	Ph (09) 5800 005	Fax (09) 5799 963
Wellington	Ph (04) 5685 949	Fax (04) 5686 376
Christchurch	Ph (03) 3843 029	Fax (03) 3849 779

Technical Services Toll Free: 1800 224 070