

# ARDEX WPM 179 SINGLE COMPONENT RUBBER WATERPROOFING MEMB.

Chemwatch Independent Material Safety Data Sheet

Issue Date: 9-Dec-2010

NC317ECP

CHEMWATCH 25-4916

Version No:2.0

CD 2010/4 Page 1 of 7

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

ARDEX WPM 179 SINGLE COMPONENT RUBBER WATERPROOFING MEMB.

### SYNONYMS

"Ardex WPM 179 Single Component Rubber Waterproofing Membrane", "water proofing membrane"

### PRODUCT USE

Waterproofing membrane.

### SUPPLIER

Company: Ardex Australia Pty Ltd

Address:

20 Powers Road

Seven Hills

NSW, 2147

Australia

Telephone: 1800 224 070

Emergency Tel: 1800 224 070 (Mon- Fri, 9am- 5pm)


Fax: +61 2 9838 7817

## Section 2 - HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.

### CHEMWATCH HAZARD RATINGS



### RISK

•None under normal operating conditions.

### SAFETY

•None under normal operating conditions.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
rubber polymer		30-60
waterbased bitumen		30-50
inorganic filler		20-40
other non hazardous ingredients		10-20

continued...

---

## Section 4 - FIRST AID MEASURES

---

### SWALLOWED

- - Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

### EYE

- If this product comes in contact with eyes:
  - Wash out immediately with water.
  - If irritation continues, seek medical attention.
  - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

- If skin or hair contact occurs:
  - Flush skin and hair with running water (and soap if available).
  - Seek medical attention in event of irritation.

### INHALED

- - If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

### NOTES TO PHYSICIAN

- Treat symptomatically.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

- - There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

### FIRE FIGHTING

- - Use water delivered as a fine spray to control fire and cool adjacent area.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

### FIRE/EXPLOSION HAZARD

- - Non combustible.
- Not considered a significant fire risk, however containers may burn.

### FIRE INCOMPATIBILITY

- None known.

### HAZCHEM

None

### PERSONAL PROTECTION

Glasses:

Chemical goggles.

Gloves:

When handling larger quantities:

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### MINOR SPILLS

- - Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

### MAJOR SPILLS

- - Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment.
- Prevent spillage from entering drains, sewers or water courses.
- Recover product wherever possible.
- Put residues in labelled containers for disposal.
- If contamination of drains or waterways occurs, advise emergency services.

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

---

## Section 7 - HANDLING AND STORAGE

---

### PROCEDURE FOR HANDLING

- - Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### SUITABLE CONTAINER

- - Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

### STORAGE INCOMPATIBILITY

- Avoid contamination of water, foodstuffs, feed or seed.

### STORAGE REQUIREMENTS

- - Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

# ARDEX WPM 179 SINGLE COMPONENT RUBBER WATERPROOFING MEMB.

Chemwatch Independent Material Safety Data Sheet

Issue Date: 9-Dec-2010

NC317ECP

CHEMWATCH 25-4916

Version No:2.0

CD 2010/4 Page 4 of 7

---

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### EXPOSURE CONTROLS

#### MATERIAL DATA

ARDEX WPM 179 SINGLE COMPONENT RUBBER WATERPROOFING MEMB.:

Not available

#### PERSONAL PROTECTION

##### EYE

■ - Safety glasses with side shields

- Chemical goggles.

- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

##### HANDS/FEET

■ Wear general protective gloves, eg. light weight rubber gloves.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.

- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.

- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.

Application of a non-perfumed moisturiser is recommended.

##### OTHER

■ No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Barrier cream.
- Eyewash unit.

##### RESPIRATOR

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

##### ENGINEERING CONTROLS

■ General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.

continued...

# ARDEX WPM 179 SINGLE COMPONENT RUBBER WATERPROOFING MEMB.

Chemwatch Independent Material Safety Data Sheet

Issue Date: 9-Dec-2010

NC317ECP

CHEMWATCH 25-4916

Version No:2.0

CD 2010/4 Page 5 of 7

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Black liquid; does not mix with water.

### PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Applicable	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Immiscible
Flash Point (°C)	Not Applicable	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Applicable	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Applicable	Specific Gravity (water=1)	Not Available
Lower Explosive Limit (%)	Not Applicable	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

## Section 10 - STABILITY AND REACTIVITY

### CONDITIONS CONTRIBUTING TO INSTABILITY

■ - Presence of incompatible materials.

- Product is considered stable.

- Hazardous polymerisation will not occur.

*For incompatible materials - refer to Section 7 - Handling and Storage.*

## Section 11 - TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

■ The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

##### EYE

■ Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

##### SKIN

■ The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives .

continued...

## ARDEX WPM 179 SINGLE COMPONENT RUBBER WATERPROOFING MEMB.

Chemwatch Independent Material Safety Data Sheet

Issue Date: 9-Dec-2010

NC317ECP

CHEMWATCH 25-4916

Version No:2.0

CD 2010/4 Page 6 of 7

### Section 11 - TOXICOLOGICAL INFORMATION

---

#### INHALED

■ The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

#### CHRONIC HEALTH EFFECTS

■ Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

#### TOXICITY AND IRRITATION

ARDEX WPM 179 SINGLE COMPONENT RUBBER WATERPROOFING MEMB.:

■ Not available. Refer to individual constituents.

---

### Section 12 - ECOLOGICAL INFORMATION

---

ARDEX WPM 179 SINGLE COMPONENT RUBBER WATERPROOFING MEMB.:

---

### Section 13 - DISPOSAL CONSIDERATIONS

---

■ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

---

### Section 14 - TRANSPORTATION INFORMATION

---

#### HAZCHEM:

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, UN, IATA, IMDG

continued...

## ARDEX WPM 179 SINGLE COMPONENT RUBBER WATERPROOFING MEMB.

Chemwatch Independent Material Safety Data Sheet

Issue Date: 9-Dec-2010

NC317ECP

CHEMWATCH 25-4916

Version No:2.0

CD 2010/4 Page 7 of 7

---

### Section 15 - REGULATORY INFORMATION

---

POISONS SCHEDULE None

#### REGULATIONS

No data for Ardex WPM 179 Single Component Rubber Waterproofing Memb. (CW: 25-4916)

---

### Section 16 - OTHER INFORMATION

---

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 9-Dec-2010

Print Date: 9-Dec-2010

*This is the end of the MSDS.*