

Ardex WPM 180

Chemwatch Material Safety Data Sheet
Issue Date: 15-Oct-2010
NC317TCP

Hazard Alert Code: **LOW**

CHEMWATCH 4576-31
Version No:3
CD 2010/1 Page 1 of 13

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

Ardex WPM 180

SYNONYMS

"water-proof membrane", "water-proofing polymer bitumen sheeting in rolls", "Shelterbit 180 Membrane"

PRODUCT USE

Water-proofing membrane.

SUPPLIER


Company: Ardex Australia Pty Ltd
Address:
20 Powers Road
Seven Hills
NSW, 2147
Australia
Telephone: 1800 224 070
Emergency Tel: **1800 224 070 (Mon- Fri, 9am- 5pm)**
Fax: +61 2 9838 7817

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.

CHEMWATCH HAZARD RATINGS



RISK

■ Vapours may cause drowsiness and dizziness.

SAFETY

- Avoid contact with skin.
- Wear eye/ face protection.
- Use only in well ventilated areas.
- Keep container in a well ventilated place.
- In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

continued...

Ardex WPM 180

Chemwatch Material Safety Data Sheet

Issue Date: 15-Oct-2010

NC317TCP

Hazard Alert Code: LOW

CHEMWATCH 4576-31

Version No:3

CD 2010/1 Page 2 of 13

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
bitumen (petroleum)	8052-42-4	30-60
thermoplastic polymer		30-60

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

SKIN

- If skin or hair contact occurs:
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

In case of burns:

- Immediately apply cold water to burn either by immersion or wrapping with saturated clean cloth.
- DO NOT remove or cut away clothing over burnt areas. DO NOT pull away clothing which has adhered to the skin as this can cause further injury.
- DO NOT break blister or remove solidified material.
- Quickly cover wound with dressing or clean cloth to help prevent infection and to ease pain.
- For large burns, sheets, towels or pillow slips are ideal; leave holes for eyes, nose and mouth.
- DO NOT apply ointments, oils, butter, etc. to a burn under any circumstances.
- Water may be given in small quantities if the person is conscious.
- Alcohol is not to be given under any circumstances.
- Reassure.
- Treat for shock by keeping the person warm and in a lying position.
- Seek medical aid and advise medical personnel in advance of the cause and extent of the injury and the estimated time of arrival of the patient.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

- Treat symptomatically.

continued...

Ardex WPM 180

Chemwatch Material Safety Data Sheet

Issue Date: 15-Oct-2010

NC317TCP

Hazard Alert Code: LOW

CHEMWATCH 4576-31

Version No:3

CD 2010/1 Page 3 of 13

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Combustible. Will burn if ignited.

Slight fire hazard when exposed to heat or flame.

NOTE: Burns with intense heat. Produces melting, flowing, burning liquid and dense acrid black smoke.

FIRE INCOMPATIBILITY

- Avoid contamination with strong oxidising agents as ignition may result.

HAZCHEM

None

PERSONAL PROTECTION

Glasses:

Not normally required.

Gloves:

When handling larger quantities:

Respirator:

Type A- P Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Sweep up.
- Collect recoverable product into labelled containers for recycling.
Place in suitable containers for disposal.

MAJOR SPILLS

- Clean up all spills immediately.
- Secure load if safe to do so.
- Bundle/collect recoverable product.
- Collect remaining material in containers with covers for disposal.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

continued...

Ardex WPM 180

Hazard Alert Code: LOW

Chemwatch Material Safety Data Sheet

Issue Date: 15-Oct-2010

NC317TCP

CHEMWATCH 4576-31

Version No:3

CD 2010/1 Page 4 of 13

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Atmosphere should be checked against exposure standards
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Always wash hands with soap and water after handling.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.

SUITABLE CONTAINER

- Packaging as recommended by manufacturer.
- Check that containers are clearly labelled.

STORAGE INCOMPATIBILITY

- Avoid storage with oxidisers.

STORAGE REQUIREMENTS

- Store in a cool area and away from sunlight.
 - Keep dry.
 - Store under cover.
 - Protect containers against physical damage.
 - Observe manufacturer's storing and handling recommendations.
- Store between temperatures of 0 and 40 deg. C.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: *May be stored together*

O: *May be stored together with specific preventions*

X: *Must not be stored together*

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
Australia Exposure Standards	bitumen (petroleum) (Bitumen fumes)		5						

continued...

Ardex WPM 180

Hazard Alert Code: LOW

Chemwatch Material Safety Data Sheet

Issue Date: 15-Oct-2010

NC317TCP

CHEMWATCH 4576-31

Version No:3

CD 2010/1 Page 5 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

MATERIAL DATA

ARDEX WPM 180:

- None assigned. Refer to individual constituents.

BITUMEN (PETROLEUM):

- bitumen (asphalt) fumes [8052-42-4]

TLV* TWA: 0.5 mg/m³ A4 asphalt (petroleum, bitumen) fume, as benzene soluble aerosol

ES* TWA: 5 mg/m³ as fumes

OES* TWA: 5 mg/m³; STEL: 10 mg/m³ as fumes

Based on surveys of asphalt workers in oil refineries and in the roofing industry the TLV-TWA is thought to reduce the risk of possible carcinogenicity.

Odour Threshold Value for hydrogen sulfide: 0.0011 ppm (detection), 0.0045 ppm (recognition)

NOTE: Detector tubes for hydrogen sulfide, measuring in excess of 0.5 ppm are available commercially.

The TLV-TWA is protective against sudden death, eye irritation, neurasthenic symptoms such as fatigue, headache, dizziness, and irritability, or permanent central nervous system effects that may result from acute, subchronic, or acute exposure to hydrogen sulfide. The offensive odour of hydrogen sulfide does not give a reliable warning signal because olfactory fatigue occurs at concentrations of 150 to 200 ppm.

Hydrogen sulfide is probably the leading cause of sudden death in the workplace. Lethal hydrogen sulfide toxicity following inhalation of 1000-2000 ppm paralyses the respiratory centre and causes breathing to stop. At concentrations between 500 to 1000 ppm, the carotid bodies are stimulated causing hypernea which is followed by apnea. Low concentrations

(50-1500 ppm) produce eye and respiratory tract irritation. Prolonged exposure to concentrations of the order of 250-500 ppm may produce pulmonary oedema although 50 ppm has also reportedly produced this effect.

Concentrations in excess of 50 ppm produce acute conjunctivitis with pain, lachrymation and photophobia.

These acute changes may progress to keratoconjunctivitis and vesiculation of the corneal epithelium.

Concentrations between 5 and 30 ppm produce ocular toxicity.

Odour Safety Factor(OSF)

OSF=1.2E3 (HYDROGEN SULFIDE).

PERSONAL PROTECTION



EYE

- No special equipment for minor exposure i.e. when handling small quantities.

• OTHERWISE:

• Safety glasses with side shields.

• Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

continued...

Ardex WPM 180

Hazard Alert Code: LOW

Chemwatch Material Safety Data Sheet

Issue Date: 15-Oct-2010

NC317TCP

CHEMWATCH 4576-31

Version No:3

CD 2010/1 Page 6 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HANDS/FEET

■ No special equipment needed when handling small quantities.

OTHERWISE: Wear chemical protective gloves, eg. PVC.

When handling hot material, wear, • Protective gloves eg. Leather gloves or gloves with Leather facing.

• Safety footwear.

OTHER

■ No special equipment needed when handling small quantities.

OTHERWISE:

• Overalls.

• Barrier cream.

• Eyewash unit.

RESPIRATOR

■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	A- AUS P	-
1000	50	-	A- AUS P
5000	50	Airline *	-
5000	100	-	A- 2 P
10000	100	-	A- 3 P
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

■ Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator.

Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:
solvent, vapours, degreasing etc., evaporating from tank (in still air).
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)

Air Speed:
0.25- 0.5 m/s (50- 100 f/min.)
0.5- 1 m/s (100- 200 f/min.)

continued...

Ardex WPM 180

Hazard Alert Code: LOW

Chemwatch Material Safety Data Sheet

Issue Date: 15-Oct-2010

NC317TCP

CHEMWATCH 4576-31

Version No:3

CD 2010/1 Page 7 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance value only.

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Black sheeting in rolls with a mild bituminous odour; insoluble in water.

PHYSICAL PROPERTIES

Does not mix with water.

Sinks in water.

State	Manufactured	Molecular Weight	Not applicable
Melting Range (°C)	>100 approx.	Viscosity	Not available
Boiling Range (°C)	470 (bitumen)	Solubility in water (g/L)	Immiscible
Flash Point (°C)	230 (bitumen)	pH (1% solution)	Not applicable
Decomposition Temp (°C)	Not available	pH (as supplied)	Not applicable
Autoignition Temp (°C)	485 (bitumen)	Vapour Pressure (kPa)	Not applicable
Upper Explosive Limit (%)	Not applicable	Specific Gravity (water=1)	1.0- 1.5 (bulk)
Lower Explosive Limit (%)	Not applicable	Relative Vapour Density (air=1)	Not applicable
Volatile Component (%vol)	Not applicable	Evaporation Rate	Not applicable

continued...

Ardex WPM 180

Chemwatch Material Safety Data Sheet

Issue Date: 15-Oct-2010

NC317TCP

Hazard Alert Code: LOW

CHEMWATCH 4576-31

Version No:3

CD 2010/1 Page 8 of 13

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- The material is discomforting to the gastro-intestinal tract.

Not normally a hazard due to physical form of product.

EYE

- Not normally a hazard due to physical form of product.

Molten material is capable of causing severe damage with loss of sight.

The vapour from heated material is discomforting to the eyes.

SKIN

- The material is discomforting to the skin.

Molten material is capable of causing burns.

INHALED

- Not normally a hazard due to physical form of product.

The vapour from the molten material is discomforting to the upper respiratory tract and lungs and may be harmful if exposure is prolonged and may even cause in some cases, sensitisation.

Inhalation of vapour may result in nausea, headache.

CHRONIC HEALTH EFFECTS

- Principal routes of exposure are usually by skin contact and inhalation of vapour from heated material.

TOXICITY AND IRRITATION

ARDEX WPM 180:

- Not available. Refer to individual constituents.

BITUMEN (PETROLEUM):

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

- Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating

continued...

Ardex WPM 180

Hazard Alert Code: LOW

Chemwatch Material Safety Data Sheet

Issue Date: 15-Oct-2010

NC317TCP

CHEMWATCH 4576-31

Version No:3

CD 2010/1 Page 9 of 13

Section 11 - TOXICOLOGICAL INFORMATION

inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

Section 12 - ECOLOGICAL INFORMATION

BITUMEN (PETROLEUM):

■ for bitumens/ asphalts:

This family of hydrocarbon is expected to have similar boiling points, vapor pressures, log Kow values (>10), and water solubilities. Limited environmental fate data also support the grouping of bitumens/ asphalts under one category. Bitumen/ asphalts contain complex hydrocarbon mixtures with molecular weights ranging from 500-2000 and carbon numbers predominantly higher than C25, vapor pressures are negligible. The high molecular weights and similar hydrocarbon distributions among the bitumens/ asphalts support the conclusion that the toxicity of this group, in general, is not expected to vary significantly across members.

Environmental fate:

Upon release to the environment, bitumens/ asphalts are expected to distribute similarly because of their low volatility and limited water solubility. Bitumen/ asphalts are expected to be resistant to biodegradation, and those components that are soluble in water are expected to be resistant to hydrolysis. When bitumen/ asphalts are heated to facilitate paving or roofing applications, the lighter, more volatile components are distilled into the atmosphere. They condense as they cool, forming small droplets of liquid known as bitumen or asphalt fume condensate. The majority of hydrocarbons in bitumen/ asphalts are not susceptible to direct photolysis, since they do not have functional groups that absorb sunlight greater than 290 nm. However, certain aromatic and unsaturated compound members have the potential to undergo photolysis because they absorb light in the environmental UV region. Since bitumens/ asphalts contain high molecular weight hydrocarbons, partitioning to the atmosphere is not considered to be important.

When compositionally analysing bitumens/ asphalts for certain toxicity endpoints the percentage of 3- to 7-ring polyaromatic hydrocarbons (PAHs) is important. The levels of 3- to 7-ring PAHs are expected to be low considering the processes used to manufacture these substances.. Fumes generated experimentally at high temperatures are more likely to contain carcinogenic PAHs than fumes generated at the lower temperatures usually seen in field samples. Therefore, generating conditions are expected to significantly affect toxicity.

Ecotoxicity:

Bitumens/ asphalts by analogy with other high molecular weight hydrocarbons are not likely to show adverse acute or chronic ecological effects in aquatic species.

For hydrocarbons:

Environmental fate:

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some hydrocarbon will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions hydrocarbons degrade to water and carbon dioxide, while under anaerobic processes they produce water, methane and carbon dioxide.

Alkenes have low log octanol/water partition coefficients (Kow) of about 1 and estimated bioconcentration factors (BCF) of about 10; aromatics have intermediate values (log Kow values of 2-3 and BCF values of 20-200), while C5 and greater alkanes have fairly high values (log Kow values of about 3-4.5 and BCF values of 100-1,500

continued...

Ardex WPM 180

Hazard Alert Code: LOW

Chemwatch Material Safety Data Sheet

Issue Date: 15-Oct-2010

NC317TCP

CHEMWATCH 4576-31

Version No:3

CD 2010/1 Page 10 of 13

Section 12 - ECOLOGICAL INFORMATION

The estimated volatilisation half-lives for alkanes and benzene, toluene, ethylbenzene, xylene (BTEX) components were predicted as 7 days in ponds, 1.5 days in rivers, and 6 days in lakes. The volatilisation rate of naphthalene and its substituted derivatives were estimated to be slower.

Indigenous microbes found in many natural settings (e.g., soils, groundwater, ponds) have been shown to be capable of degrading organic compounds. Unlike other fate processes that disperse contaminants in the environment, biodegradation can eliminate the contaminants without transferring them across media.

The final products of microbial degradation are carbon dioxide, water, and microbial biomass. The rate of hydrocarbon degradation depends on the chemical composition of the product released to the environment as well as site-specific environmental factors. Generally the straight chain hydrocarbons and the aromatics are degraded more readily than the highly branched aliphatic compounds. The n-alkanes, n-alkyl aromatics, and the aromatics in the C10-C22 range are the most readily biodegradable; n-alkanes, n-alkyl aromatics, and aromatics in the C5-C9 range are biodegradable at low concentrations by some microorganisms, but are generally preferentially removed by volatilisation and thus are unavailable in most environments; n-alkanes in the C1-C4 ranges are biodegradable only by a narrow range of specialised hydrocarbon degraders; and n-alkanes, n-alkyl aromatics, and aromatics above C22 are generally not available to degrading microorganisms. Hydrocarbons with condensed ring structures, such as PAHs with four or more rings, have been shown to be relatively resistant to biodegradation. PAHs with only 2 or 3 rings (e.g., naphthalene, anthracene) are more easily biodegraded. In almost all cases, the presence of oxygen is essential for effective biodegradation of oil. The ideal pH range to promote biodegradation is close to neutral (6-8). For most species, the optimal pH is slightly alkaline, that is, greater than 7.

All biological transformations are affected by temperature. Generally, as the temperature increases, biological activity tends to increase up to a temperature where enzyme denaturation occurs.

Atmospheric fate: Alkanes, isoalkanes, and cycloalkanes have half-lives on the order of 1-10 days, whereas alkenes, cycloalkenes, and substituted benzenes have half-lives of 1 day or less. Photochemical oxidation products include aldehydes, hydroxy compounds, nitro compounds, and peroxyacyl nitrates. Alkenes, certain substituted aromatics, and naphthalene are potentially susceptible to direct photolysis.

Ecotoxicity:

Hydrocarbons are hydrophobic (high log Kow and low water solubility). Such substances produce toxicity in aquatic organisms by a mechanism referred to as "non-polar narcosis" or "baseline" toxicity. The hydrophobicity increases and water solubility decreases with increasing carbon number for a particular class of hydrocarbon. Substances with the same carbon number show increased hydrophobicity and decreased solubility with increasing saturation. Quantitative structure activity relationships (QSAR), relating both solubility and toxicity to Kow predict that the water solubility of single chemical substances decreases more rapidly with increasing Kow than does the acute toxicity.

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

The values of log Kow for individual hydrocarbons increase with increasing carbon number within homologous series of generic types. Quantitative structure activity relationships (QSAR), relating log Kow values of single hydrocarbons to toxicity, show that water solubility decreases more rapidly with increasing Kow than does the concentration causing effects. This relationship varies somewhat with species of hydrocarbon, but it follows that there is a log Kow limit for hydrocarbons, above which, they will not exhibit acute toxicity; this limit is at a log Kow value of about 4 to 5. It has been confirmed experimentally that for fish and invertebrates, paraffinic hydrocarbons with a carbon number of 10 or higher (log Kow >5) show no acute toxicity and that alkylbenzenes with a carbon number of 14 or greater (log Kow >5) similarly show no acute toxicity.

QSAR equations for chronic toxicity also suggest that there should be a point where hydrocarbons with high log Kow values become so insoluble in water that they will not cause chronic toxicity, that is, that there is also a solubility cut-off for chronic toxicity. Thus, paraffinic hydrocarbons with carbon numbers of greater than 14 (log Kow >7.3) should show no measurable chronic toxicity. Experimental support for this cut-off is demonstrated by chronic toxicity studies on lubricant base oils and one "heavy" solvent grade (substances composed of paraffins of C20 and greater) which show no effects after exposures to concentrations well above solubility.

The initial criteria for classification of substances as dangerous to the aquatic environment are based upon

continued...

Ardex WPM 180

Hazard Alert Code: LOW

Chemwatch Material Safety Data Sheet

Issue Date: 15-Oct-2010

NC317TCP

CHEMWATCH 4576-31

Version No:3

CD 2010/1 Page 11 of 13

Section 12 - ECOLOGICAL INFORMATION

acute toxicity data in fish, daphnids and algae. However, for substances that have low solubility and show no acute toxicity, the possibility of a long-term or chronic hazard to the environment is recognised in the R53 phrase or so-called "safety net". The R53 assignment for possible long-term harm is a surrogate for chronic toxicity test results and is triggered by substances that are both bioaccumulative and persistent. The indicators of bioaccumulation and persistence are taken as a BCF > 100 (or log Kow > 3 if no BCF data) and lack of ready biodegradability. For low solubility substances which have direct chronic toxicity data demonstrating no chronic toxicity at 1 mg/L or higher, these data take precedence such that no classification for long term toxicity is required.

Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

For hydrogen sulfide:

Environmental fate:

Since hydrogen sulfide exists as a gas at atmospheric pressure, partitioning to the air is likely to occur after environmental releases. However, the compound is also soluble in oil and water, and therefore, may partition as well to surface water, groundwater, or moist soil. In addition, sorption of hydrogen sulfide from air onto soil and plant foliage occurs. Hydrogen sulfide's solubility in pure water varies with temperature from 5.3 g/L at 10 °C to 3.2 g/L at 30 C. Once hydrogen sulfide is dissolved in water, it will dissociate into bisulfide ion (HS⁻) and sulfide ion (S²⁻); the ratio of the concentrations of these various ions will depend on the pH of the solution. Hydrogen sulfide can also form insoluble sulfide salts with various metals (i.e., copper, zinc, nickel, and iron) that may be present in soils or environmental waters . Hydrogen sulfide evaporates easily from water, and the rate of evaporation depends on factors such as temperature, humidity, pKa, pH, and the concentration of certain metal ions. Hydrogen sulfide will cross the air-water interface with kinetics similar to other unreactive gases, such as oxygen (O₂), nitrogen (N₂), and carbon dioxide (CO₂), at pHs <=6. At higher pHs, such as seawater, which has a pH of 8 or greater, hydrogen sulfide escape is enhanced due to an ionic species gradient in the water close to the surface. Complexation of bisulfide and sulfide ions to trace metal ions (i.e., Zn²⁺, Co²⁺, and Ni²⁺) found in seawater will also have an effect on the transport of hydrogen sulfide across the air-water interface.

Clay or organic matter may sorb hydrogen sulfide. Under natural conditions, it is likely that some of the hydrogen sulfide would be oxidized to sulfate, which may be removed by leaching or taken up by plants. This, in turn, may make gas sorption sites available for additional sorption. Several species of soil, aquatic, and marine microorganisms oxidize hydrogen sulfide to elemental sulfur, and its half-time in these environments usually ranges from 1 hour to several hours .Food chain bioconcentration and biomagnification are unlikely. In the atmosphere, hydrogen sulfide may be oxidized by oxygen (O₂) and ozone (O₃) to give sulfur dioxide (SO₂), and ultimately sulfate compounds. Sulfur dioxide and sulfates are eventually removed from the atmosphere through absorption by plants, deposition on and sorption by soils, or through precipitation. A residence time of approximately 1.7 days at an ozone concentration of 0.05 mg/m³ has been calculated for hydrogen sulfide. The effective life-times for hydrogen sulfide based on summer daytime and yearly average hydroxyl radical concentrations have been estimated to be 0.23 and 2.3 days, respectively, based a measured rate constant of 4.8x10⁻¹² cm³/molecule second. Life-times in air ranging from approximately 1 day in the summer to 42 days in the winter have been estimated for hydrogen sulfide. Hydrogen sulfide is not expected to be decomposed by direct absorption of ultraviolet radiation and the reaction with ozone is not expected to be a significant environmental fate.

In aqueous solution, hydrogen sulfide is a weak acid, exhibiting two acid dissociation constants. The first dissociation yields bisulfide ion (HS⁻), and the second yields sulfide ion (S²⁻), with pKa values for each of these dissociations of 7.04 and 11.96, respectively. At a pH of 7.0, the ratio of the concentration of aqueous hydrogen sulfide to bisulfate ion is approximately 1-to-1. As the pH increases above 7.0, the ratio of the concentration of bisulfide ion to aqueous hydrogen sulfide increases. At a pH of 8, the ratio of the concentration of bisulfide ion to the concentration of aqueous hydrogen sulfide is approximately 10-to-1. The relative concentration of sulfide ion does not begin to increase until a pH of 11 is exceeded; only above pH 12 will the concentration of sulfide ion become significant (>50%). Hydrogen sulfide oxidation by O₂ readily occurs in surface waters. At 25 °C and pH 8, half-times of 50 and 26 hours were reported for hydrogen sulfide in water and seawater, respectively. Above pH 8, however, the rate of oxidation was independent of pH. Hydrogen sulfide in waste water may be controlled by addition of oxidizing chemicals, which react to form less toxic byproducts. In warm, damp environments (such as manholes and gravity sewers), hydrogen sulfide may

continued...

Ardex WPM 180

Hazard Alert Code: LOW

Chemwatch Material Safety Data Sheet

Issue Date: 15-Oct-2010

NC317TCP

CHEMWATCH 4576-31

Version No:3

CD 2010/1 Page 12 of 13

Section 12 - ECOLOGICAL INFORMATION

be oxidized by autotrophic bacteria to sulfuric acid. Chemical oxidation of hydrogen sulfide dissolved in sewage water produces sulfur at pH 6–7, while sulfur, polysulfides, thiosulfates, and ultimately sulfate are formed at pHs of 7–9.

Hydrogen sulfide is one of the principal components in the natural sulfur cycle. Bacteria, fungi, and actinomycetes (a fungus-like bacteria) release hydrogen sulfide during the decomposition of sulfur containing proteins and by the direct reduction of sulfate (SO₄²⁻). Hydrogen sulfide is also consumed by bacteria found in soil and water that oxidize hydrogen sulfide to elemental sulfur. Photosynthetic bacteria can oxidize hydrogen sulfide to sulfur and sulfate in the presence of light and the absence of oxygen.

A number of microorganisms have been found to degrade hydrogen sulfide to elemental sulfur or sulfate. Among these are a heterotrophic bacterium of the genus *Xanthomonas* isolated from dimethyl disulfide-acclimated peat, heterotrophic fungi, and a marine isopod. Soils may sorb considerable amounts of hydrogen sulfide from the air, retaining most of it in the form of elemental sulfur. Manganese compound found in these soils appeared to catalyze the oxidation of hydrogen sulfide to elemental sulfur

Ecotoxicity:

Fish LC50 (96 h): 0.75->0.4 mg/l.

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM:

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE None

REGULATIONS

Regulations for ingredients

bitumen (petroleum) (CAS: 8052-42-4) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "OECD Representative List of High Production Volume (HPV) Chemicals"

No data for Ardex WPM 180 (CW: 4576-31)

continued...

Ardex WPM 180

Hazard Alert Code: LOW

Chemwatch Material Safety Data Sheet

Issue Date: 15-Oct-2010

NC317TCP

CHEMWATCH 4576-31

Version No:3

CD 2010/1 Page 13 of 13

Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 15-Oct-2010

Print Date: 3-Feb-2011

This is the end of the MSDS.